


ITEM TECHNICAL CARD



diámetro vite	M5
E (mm)	0,45
G (mm)	6,0
tipo	DGQXX955A
A (mm)	13,2
C (mm)	8,3
B (mm)	12,8
s - spessore lamiera (mm)	0,7 - 1,6
D (mm)	7,7
foro lamiera (mm)	9,5x9,5
F (mm)	13,3

DESCRIZIONE \ DESCRIPTION:					CATEGORIA \ CATEGORY:		2734600.00500		
DadoOX Gab.OX ss0,7-1,6 a.9,5x9,5(955AXX) M5									
MATERIAL \ MATERIAL:			TRATTAMENTO TERMICO \ HEAT TREATMENT:			NOTE \ NOTES:			
ESEGUITO DA \ DRAWN BY:		DATA:	TRATT. SUPERFICIALE\ SURF. TREATMENT:		Rugosità superficiale generale: General surface roughness:				
RIVIT									
CONTROLLATO DA \ CHECKED BY:		DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:			NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW			
RIVIT									
APPROVATO DA \ APPROVED BY:		DATA:	DUREZZA \ HARDNESS:	FOGLIO\ SHEET:	FORMATO FOGLIO:	A4	METODO 1 (ISO 128)	REVISIONE:	
RIVIT				1 OF 1	SHEET FORMAT:		METHOD 1 (ISO 128)	REVISION:	
			PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07		