

ITEM TECHNICAL CARD



Lochdurchmesser (mm)	4,1
d - Blindnieten durchmesser	4,0
T - Kopfbreite (mm)	8,0
L - länge der niete (mm)	16,0
k - Kopf Dicke (mm)	1,0
Schiere Stärke (N)	1200
Zugbruchlast (N)	1700
Klemmbereich (mm)	10,0 ÷ 12,0
Körpermaterial	Aluminium
Nagelmaterial	Stahl
Kopftyp	flachrundkopf

DESCRIZIONE \ DESCRIPTION: <b>AFT-Blind rivet Alu/Steel DH 4,0x16,0</b>		CATEGORIA \ CATEGORY:		<b>0004300.05000</b>
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:	
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>	
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: <b>1 OF 1</b>	METODO 1 (ISO 128) METHOD 1 (ISO 128) REVISIONE: REVISION: 
		PESO \ WEIGHT:	Scale \ SCALE: <b>Mod.P023_07</b>	
				<b>FASTENERS &amp; TOOLS</b>  <b>RIVIT.IT</b>