

ITEM TECHNICAL CARD



Lochdurchmesser (mm)	4,1
d - Blindnieten durchmesser	4,0
T - Kopfbreite (mm)	10,0
L - länge der niete (mm)	12,0
k - Kopf Dicke (mm)	1,5
Schiere Stärke (N)	1200
Zugbruchlast (N)	1700
Klemmbereich (mm)	6,0 ÷ 8,0
Körpermaterial	Aluminium
Nagelmaterial	Stahl
Kopftyp	gross

DESCRIZIONE \ DESCRIPTION: AFL10-Blind rivet Alu/Steel LH10 4,0x12,0 TL10		CATEGORIA \ CATEGORY: 0012100.00500	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:	NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	METODO 1 (ISO 128) REVISIONE: METHOD 1 (ISO 128) REVISION:
		PESO \ WEIGHT:	Scale \ SCALE: Mod.P023_07



**FASTENERS
& TOOLS**
RIVIT.IT