

ITEM TECHNICAL CARD



Lochdurchmesser (mm)	5,0
d - Blindnieten durchmesser	4,8
T - Kopfbreite (mm)	9,5
L - länge der niete (mm)	20,0
k - Kopf Dicke (mm)	1,1
Schiere Stärke (N)	2900
Zugbruchlast (N)	3700
Klemmbereich (mm)	14,0 ÷ 16,0
Körpermaterial	Stahl
Nagelmaterial	Stahl
Kopftyp	flachrundkopf

DESCRIZIONE \ DESCRIPTION: <b>FFT-Blind rivet Steel/Steel DH 4,8x20,0</b>		CATEGORIA \ CATEGORY: <b>0032800.03000</b>	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:	NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	FUOGILIO \ SHEET: <b>1 OF 1</b> FORMATO FUGILIO: <b>A4</b> SHEET FORMAT: <b>A4</b>
		PESO \ WEIGHT:	CARTIGLIO \ FORMAT <b>Mod.P023_07</b> 



**FASTENERS  
& TOOLS**  
RIVIT.IT