


ITEM TECHNICAL CARD



Lochdurchmesser (mm)	6,1
d - Blindnieten durchmesser	6,0
T - Kopfbreite (mm)	12,0
L - länge der niete (mm)	22,0
k - Kopf Dicke (mm)	1,5
Schiere Stärke (N)	4000
Zugbruchlast (N)	5600
Klemmbereich (mm)	13,0 ÷ 16,0
Körpermaterial	Stahl
Nagelmaterial	Stahl
Kopftyp	flachrundkopf

DESCRIZIONE \ DESCRIPTION: FFT-Blind rivet Steel/Steel DH 6,0x22,0		CATEGORIA \ CATEGORY: 0034000.02000	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:	NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FUOGGIO \ SHEET: 1 OF 1 FORMATO FOGGIO: A4 SHEET FORMAT: A4
		PESO \ WEIGHT:	CARTIGLIO \ FORMAT Mod.P023_07



FASTENERS & TOOLS
RIVIT.IT