





ITEM TECHNICAL CARD



Lochdurchmesser (mm)	5,0 - 5,2
durchmesser der bolzen (mm)	4,8
T - Kopfbreite (mm)	10,0
L1 - Bolzenlänge (mm)	41,5
L2 (mm)	12,3 - 14,0
K - épaisseur de la tête (mm)	3,2
Schiere Stärke (N)	10800
Modell	RLFT06-04
Zugbruchlast (N)	9700
Klemmbereich (mm)	4,8 ÷ 7,9

DESCRIZIONE \ DESCRIPTION: RIVLOCK-Lockbolt Steel d.4,8 gr 4,8-7,9 DH RLFT 6-4 d4,8			CATEGORIA \ CATEGORY: 0351300.00100	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:	
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW	
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07
			 	
			 FASTENERS & TOOLS  RIVIT.IT	