

ITEM TECHNICAL CARD



Lochdurchmesser (mm)	8,2 - 8,4
durchmesser der bolzen (mm)	8,0
T - Kopfbreite (mm)	16,7
L1 - Bolzenlänge (mm)	61,5
L2 (mm)	27,7 - 29,3
K - épaisseur de la tête (mm)	5,2
Schiere Stärke (N)	29800
Modell	RLFT10-10
Zugbruchlast (N)	26700
Klemmbereich (mm)	12,7 ÷ 19,1

DESCRIZIONE \ DESCRIPTION: <b>RIVLOCK-Lockbolt Steel d.8,0 gr 12,7-19,1 DH RLFT 10-10 d8,0</b>		CATEGORIA \ CATEGORY: <b>0352700.00500</b>	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:	NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	METODO 1 (ISO 128) REVISIONE: METHOD 1 (ISO 128) REVISION:
		PESO \ WEIGHT:	Scale \ SCALE: <b>Mod.P023_07</b>



**FASTENERS  
& TOOLS**  
RIVIT.IT