



ITEM TECHNICAL CARD

Anzugsmoment (Nm)	25,0
Lochdurchmesser (mm)	14,0
Modell	RHAF08
Dübellänge (mm)	50,0
minimale Lochtiefe (mm)	65,0
profondità posa (mm)	50,0
für Schrauben	M8
Klemmbereich max (mm)	10,0
zulässige Belastung (daN)	450,0

DESCRIZIONE \ DESCRIPTION: RHA/F-Steel anchor only head h.14,0 M8x50				CATEGORIA \ CATEGORY:		0364800.00050		
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:		 FASTENERS & TOOLS  RIVIT.IT		
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:					
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW					
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4	METODO 1 (ISO 128) METHOD 1 (ISO 128)			REVISIONE: REVISION:
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07	