


ITEM TECHNICAL CARD

Länge (mm)	19,0
Material	weiß verzinkter Stahl C15
Durchmesser	4,2
pitch	1,41
UNI	8117
DIN	7504K
ISO	15480
k (mm)	4,0
S (mm)	7,0
Normative Beschreibung	Sechskantkopf Bohrschraube gefälscht Unterlegscheibe
d1 (mm)	8,8

DESCRIZIONE \ DESCRIPTION: Hexagon flange head self-drilling screw UNI 8117/DIN 7504K white		CATEGORIA \ CATEGORY: 04848ZB.01000	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:	NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	METODO 1 (ISO 128) METHOD 1 (ISO 128)
		FOGLIO \ SHEET: 1 OF 1	REVISIONE: REVISION:
		PESO \ WEIGHT:	CARTIGLIO \ FORMAT Mod.P023_07
		Scale \ SCALE:	



**FASTENERS
& TOOLS**
RIVIT.IT