


ITEM TECHNICAL CARD



Schlag pro Minute	3000
Gesamtlänge (mm)	170
Gewicht (kg)	1,6
Geräuschpegel dB(A)	99
Vibrationen (m/s ²)	5,5
Luftverbrauch (l/min)	300 nl/1'
	6,2
round tool handle (mm)	10,2
air connector	G 1/4

DESCRIZIONE \ DESCRIPTION: Pneumatic riveting gun Punches on demand ET-F15				CATEGORIA \ CATEGORY: 0589200	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:		
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW		
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4	METODO 1 (ISO 128) METHOD 1 (ISO 128) REVISIONE: REVISION:
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07	



**FASTENERS
& TOOLS**
RIVIT.IT