



ITEM TECHNICAL CARD

d - Kabeldurchmesser (mm)	1,5
Ds - Steckerdurchmesser (mm)	22,8
Df - Lochdurchmesser (mm)	19,8
Lo - freie Länge (mm)	22,0
Fn - Belastung max (kgf)	2,72
Ln - Federlänge (mm)	11,6
fn - Frühlingspfeil (mm)	10,4
Rg - Federsteifigkeit (kgf/mm)	0,261

DESCRIZIONE \ DESCRIPTION: Druckfeder C70 - Stahl weiß verzinkt CO.40/196				CATEGORIA \ CATEGORY:		0607100	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:			
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:				
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:		NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW			
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4	METODO 1 (ISO 128) METHOD 1 (ISO 128)	REVISIONE: REVISION:	FASTENERS & TOOLS 
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07	