



ITEM TECHNICAL CARD

Material	weiß verzinkter Stahl kl.8
Durchmesser	M39
pitch	4,0
UNI	7473
DIN	982
ISO	7040
m (mm)	31,2
S (mm)	60,0
Normative Beschreibung	Hohe Selbstsichernde Sechskantmutter mit Polyamidring
h (mm)	42,0

DESCRIZIONE \ DESCRIPTION: <b>Selbstsichernde Sechskantmutter U7473/D982 Kl.8 - Stahl weiß</b>				CATEGORIA \ CATEGORY:		<b>07667ZB</b>	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:			
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:		Rugosità superficiale generale: General surface roughness:			
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:		<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>		 <b>FASTENERS &amp; TOOLS</b> RIVIT.IT	
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: <b>1 OF 1</b>	FORMATO FOGLIO: SHEET FORMAT: <b>A4</b>	METODO 1 (ISO 128) METHOD 1 (ISO 128)		
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT <b>Mod.P023_07</b>	