


ITEM TECHNICAL CARD

TX	30
Länge (mm)	80/50,0
Material	gelb verzinkter Stahl C10B21
Durchmesser	6,0
pitch	4,7
D max (mm)	12,1
d1 (mm)	4,8

DESCRIZIONE \ DESCRIPTION: <b>Truciolare perforante rapid svasante TSP TX T30 ZG 6x80/50</b>				CATEGORIA \ CATEGORY: <b>08436ZG.00200</b>	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:		
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>		
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: <b>1 OF 1</b>	FORMATO FOGLIO: SHEET FORMAT: <b>A4</b>	METODO 1 (ISO 128) METHOD 1 (ISO 128)
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT <b>Mod.P023_07</b>	REVISIONE: REVISION: 



**FASTENERS  
& TOOLS**  
RIVIT.IT