

ITEM TECHNICAL CARD

Länge (mm)	16
Material	vermessingter Stahl C15
Durchmesser	3
DIN	7505A
Normative Beschreibung	Kreuzsenkkopf Befestigungselemente
D min/max (mm)	5,7/6,0
K max (mm)	1,8
r1~ (mm)	1,5
b max (mm)	0,8
N Pozi Recess	1
recess m ~	3

DESCRIZIONE \ DESCRIPTION: <b>Flat head chipboard screw DIN 7505A brass plated steel C15 3x16</b>		CATEGORIA \ CATEGORY:		<b>08722OT.01000</b>
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:	
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:		<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: <b>1 OF 1</b>	
		PESO \ WEIGHT:	Scale \ SCALE:	METODO 1 (ISO 128) METHOD 1 (ISO 128)
			CARTIGLIO \ FORMAT <b>Mod.P023_07</b>	REVISIONE: REVISION:



**FASTENERS  
& TOOLS**  
RIVIT.IT