


ITEM TECHNICAL CARD

Länge (mm)	19,0
Material	weiß verzinkter Stahl C15
Durchmesser	6,3
pitch	1,8
UNI	6955
DIN	7982C
ISO	7050
Normative Beschreibung	Kreuzsenkkopf Blechschraube
r max (mm)	2,4
K (mm)	3,8
d1 (mm)	12,4
PH	3

DESCRIZIONE \ DESCRIPTION: <b>Phillips cross flat head tapping screw UNI 6955/DIN 7982 white zinc</b>				CATEGORIA \ CATEGORY: <b>10624ZB.00200</b>	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:		
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>		
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: <b>1 OF 1</b>	FORMATO FOGLIO: SHEET FORMAT: <b>A4</b>	METODO 1 (ISO 128) METHOD 1 (ISO 128) REVISIONE: REVISION:
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT <b>Mod.P023_07</b>	



**FASTENERS  
& TOOLS**  
RIVIT.IT