


ITEM TECHNICAL CARD

d. - Durchmesser (mm)	6
Spitzendurchmesser (mm)	6
Länge (mm)	50
minimale Bohrtiefe (mm)	55
Klemmbereich (mm)	20

DESCRIZIONE \ DESCRIPTION: NLV-Extended nylon anchor w/FCH screw PZ2 d.4,0x55 d.6x50				CATEGORIA \ CATEGORY: 1105600.00100	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:		
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW		
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4	METODO 1 (ISO 128) METHOD 1 (ISO 128)
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07	REVISIONE: REVISION: 



**FASTENERS
& TOOLS**
RIVIT.IT