

ITEM TECHNICAL CARD



Lochdurchmesser (mm)	3,5
d - Blindnieten durchmesser	3,4
T - Kopfbreite (mm)	7,0
L - länge der niete (mm)	7,0
k - Kopf Dicke (mm)	0,9
Schiere Stärke (N)	1000
Zugbruchlast (N)	1400
Klemmbereich (mm)	1,5 ÷ 3,5
Körpermaterial	Kupfer
Nagelmaterial	Stahl
Kopftyp	flachrundkopf

DESCRIZIONE \ DESCRIPTION: RFT-Blind rivet Copper/Steel DH 3,4x7,0		CATEGORIA \ CATEGORY: 1186400.10000	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:	NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	METODO 1 (ISO 128) METHOD 1 (ISO 128)
		FOGLIO \ SHEET: 1 OF 1	REVISIONE: REVISION:
		PESO \ WEIGHT:	CARTIGLIO \ FORMAT Mod.P023_07
		Scale \ SCALE:	



**FASTENERS
& TOOLS**
RIVIT.IT