


ITEM TECHNICAL CARD



Lochdurchmesser (mm)	4,0
d - Blindnieten durchmesser	3,9
T - Kopfbreite (mm)	8,0
L - länge der niete (mm)	16,0
k - Kopf Dicke (mm)	1,0
Schiere Stärke (N)	1200
Zugbruchlast (N)	1700
Klemmbereich (mm)	10,0 ÷ 12,0
Körpermaterial	Verzinkter Kupfer
Nagelmaterial	Stahl
Kopftyp	flachrundkopf

DESCRIZIONE \ DESCRIPTION: RZFT-Blind rivet Zinc plated Copper/Steel DH 3,9x16,0		CATEGORIA \ CATEGORY: 1201900.05000	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:	NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FUOGGIO \ SHEET: 1 OF 1 FORMATO FOGGIO: A4 SHEET FORMAT: A4
		PESO \ WEIGHT:	CARTIGLIO \ FORMAT: Mod.P023_07



FASTENERS & TOOLS
RIVIT.IT