


ITEM TECHNICAL CARD



Lochdurchmesser (mm)	3,25/4,0
d - Blindnieten durchmesser	3,2
T - Kopfbreite (mm)	7,2
L - länge der niete (mm)	8,0
k - Kopf Dicke (mm)	0,85
Schiere Stärke (N)	800
Zugbruchlast (N)	900
Klemmbereich (mm)	0,5 ÷ 4,8

DESCRIZIONE \ DESCRIPTION: MULTIGRIPRIV-Blind rivet Copper/Coppered steel gr 0,5-4,8 DH				CATEGORIA \ CATEGORY: 1245400.01000	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:		
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW		
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4	METODO 1 (ISO 128) METHOD 1 (ISO 128) REVISIONE: REVISION:
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07	



**FASTENERS
& TOOLS**
RIVIT.IT