


ITEM TECHNICAL CARD



Lochdurchmesser (mm)	4,0
d - Blindnieten durchmesser	3,9
T - Kopfbreite (mm)	8,0
L - länge der niete (mm)	12,0
Schiere Stärke (N)	1800
Zugbruchlast (N)	2800
Klemmbereich (mm)	6,0 ÷ 8,0
Körpermaterial	Kupfernickel
Nagelmaterial	Edelstahl A2
Kopftyp	Senkkopf

DESCRIZIONE \ DESCRIPTION: <b>XIS-Blind rivet Cupronickel/Stainless steel 304 CS KH6,7 3,9x12,0</b>		CATEGORIA \ CATEGORY: <b>1560400.06000</b>	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:	NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	METODO 1 (ISO 128) REVISIONE: METHOD 1 (ISO 128) REVISION:
		PESO \ WEIGHT:	Scale \ SCALE: <b>Mod.P023_07</b>



**FASTENERS  
& TOOLS**  
RIVIT.IT