


ITEM TECHNICAL CARD



Lochdurchmesser (mm)	3,3
d - Blindnieten durchmesser	3,2
T - Kopfbreite (mm)	6,5
L - länge der niete (mm)	7,0
k - Kopf Dicke (mm)	0,8
Schiere Stärke (N)	800
Zugbruchlast (N)	1100
Klemmbereich (mm)	2,0 ÷ 4,0
Körpermaterial	Aluminium
Nagelmaterial	Stahl
Kopftyp	flachrundkopf
RAL	RAL9002

DESCRIZIONE \ DESCRIPTION: <b>AFT9002-Blind rivet Alu RAL9002/Steel DH 3,2x7,0</b>				CATEGORIA \ CATEGORY: <b>1565800.01000</b>	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:			
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:		<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>	
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: <b>1 OF 1</b>	FORMATO FOGLIO: SHEET FORMAT: <b>A4</b>	METODO 1 (ISO 128) METHOD 1 (ISO 128)
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT <b>Mod.P023_07</b>	REVISIONE: REVISION:



**FASTENERS  
& TOOLS**  
RIVIT.IT