


ITEM TECHNICAL CARD



Lochdurchmesser (mm)	4,0
d - Blindnieten durchmesser	3,9
T - Kopfbreite (mm)	8,0
L - länge der niete (mm)	18,0
Schiere Stärke (N)	1800
Zugbruchlast (N)	2800
Klemmbereich (mm)	12,0 ÷ 14,0
Körpermaterial	Kupfernickel
Nagelmaterial	Edelstahl A2
Kopftyp	Senkkopf

DESCRIZIONE \ DESCRIPTION: XIS-Blind rivet Cupronickel/Stainless steel 304 CS KH7,5 3,9x18,0		CATEGORIA \ CATEGORY: 1572000.00500	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:	NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	METODO 1 (ISO 128) REVISIONE: METHOD 1 (ISO 128) REVISION:
		PESO \ WEIGHT:	Scale \ SCALE: Mod.P023_07



FASTENERS & TOOLS
RIVIT.IT