


ITEM TECHNICAL CARD

Anzugsmoment (Nm)	10,0
Lochdurchmesser (mm)	12,0
Modell	RHAB06
Dübellänge (mm)	45,0
minimale Lochtiefe (mm)	60,0
profondità posa (mm)	45,0
für Schrauben	M6x55,0
Klemmbereich max (mm)	10,0
zulässige Belastung (daN)	275,0

DESCRIZIONE \ DESCRIPTION: RHA/B-Steel anchor with screw HH M6x55 h.12,0 M6x45				CATEGORIA \ CATEGORY: 1583000.00050	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:		
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW		
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4	METODO 1 (ISO 128) METHOD 1 (ISO 128) REVISIONE: REVISION:
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07	



**FASTENERS
& TOOLS**
RIVIT.IT