


ITEM TECHNICAL CARD

Anzugsmoment (Nm)	75,0
Lochdurchmesser (mm)	20,0
Modell	RHAB12
Dübellänge (mm)	75,0
minimale Lochtiefe (mm)	95,0
profondità posa (mm)	75,0
für Schrauben	M12x90,0
Klemmbereich max (mm)	20,0
zulässige Belastung (daN)	950,0

DESCRIZIONE \ DESCRIPTION: RHA/B-Steel anchor with screw HH M12x100 h.20,0 M12x75				CATEGORIA \ CATEGORY: 1583300.00025	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:		
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW		
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4	METODO 1 (ISO 128) METHOD 1 (ISO 128) REVISIONE: REVISION:
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07	



**FASTENERS
& TOOLS**
RIVIT.IT