



ITEM TECHNICAL CARD

Anzugsmoment (Nm)	25,0
Modell	RHAG08
Dübellänge (mm)	50,0
P Haken (mm)	10,0
minimale Lochtiefe (mm)	65,0
Tipp	14,0
profondità posa (mm)	50,0
für Schrauben	M8x55,0
Klemmbereich max (mm)	10,0
zulässige Belastung (daN)	450,0

DESCRIZIONE \ DESCRIPTION: RHA/G-Steel anchor with clip h.14,0 M8x55				CATEGORIA \ CATEGORY:		1583600.00050	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:			
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:		Rugosità superficiale generale: General surface roughness:			
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:		NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW			
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4	METODO 1 (ISO 128) METHOD 1 (ISO 128)	REVISIONE: REVISION:	 FASTENERS & TOOLS RIVIT.IT
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07	