


ITEM TECHNICAL CARD

Anzugsmoment (Nm)	75,0
Modell	RHAG12
Dübellänge (mm)	75,0
P Haken (mm)	16,0
minimale Lochtiefe (mm)	95,0
Tipp	20,0
profondità posa (mm)	75,0
für Schrauben	M12x90,0
Klemmbereich max (mm)	20,0
zulässige Belastung (daN)	950,0

DESCRIZIONE \ DESCRIPTION: RHA/G-Steel anchor with clip h.20,0 M12x75				CATEGORIA \ CATEGORY: 1583800.00025	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:		
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW		
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4	METODO 1 (ISO 128) METHOD 1 (ISO 128) REVISIONE: REVISION:
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07	



**FASTENERS
& TOOLS**
RIVIT.IT