


ITEM TECHNICAL CARD



Lochdurchmesser (mm)	6,6/6,8
d - Blindnieten durchmesser	6,4
T - Kopfbreite (mm)	13,0
L - länge der niete (mm)	18,5
L1 (mm)	22,5
k - Kopf Dicke (mm)	3,0
Schiere Stärke (N)	11200
Zugbruchlast (N)	7000
Klemmbereich (mm)	10,8 ÷ 12,8
Körpermaterial	Stahl
Nagelmaterial	Stahl
Kopftyp	flachrundkopf

DESCRIZIONE \ DESCRIPTION: LOCKRIV-Blind rivet Steel/Steel gr 10,8-12,8 DH 6,4x18,5		CATEGORIA \ CATEGORY: 1594500.00250	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:	NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FUOGGIO \ SHEET: 1 OF 1 FORMATO FOGGIO: A4 SHEET FORMAT: A4
		PESO \ WEIGHT:	CARTIGLIO \ FORMAT Mod.P023_07



**FASTENERS
& TOOLS**
RIVIT.IT