





ITEM TECHNICAL CARD



Material	Rohstahl C60
Durchmesser	6,0
UNI	8842A
DIN	6798A
S (mm)	0,4
für Schrauben	M3
Innendurchmesser (mm)	3,2

DESCRIZIONE \ DESCRIPTION:		CATEGORIA \ CATEGORY:		20894GR.04500	
Serrated external lock washer UNI 8842A/DIN 6798A plain steel 3,2x6					
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY:	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale:		
<b>RIVIT</b>			General surface roughness:		
CONTROLLATO DA \ CHECKED BY:	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]:	<b>NON SCALARE IL DISEGNO</b>		
<b>RIVIT</b>		HEAT TREATMENT (SURF) DEPTH [mm]:	<b>DO NOT RESIZE THE DRAW</b>		
APPROVATO DA \ APPROVED BY:	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET:	FORMATO FOGLIO:	METODO 1 (ISO 128)
<b>RIVIT</b>			<b>1 OF 1</b>	<b>A4</b>	METHOD 1 (ISO 128)
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT	REVISIONE: REVISION:
				<b>Mod.P023_07</b>	
					<b>FASTENERS &amp; TOOLS</b>  <b>RIVIT.IT</b>