



ITEM TECHNICAL CARD

Material	weiß verzinkter Stahl C60
Durchmesser	6,0
UNI	8842A
DIN	6798A
S (mm)	0,4
für Schrauben	M3
Innendurchmesser (mm)	3,2

DESCRIZIONE \ DESCRIPTION: <b>Serrated external lock washer UNI 8842A/DIN 6798A white zinc</b>		CATEGORIA \ CATEGORY: <b>20894ZB.05000</b>	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:	NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	FUOGIO \ SHEET: <b>1 OF 1</b>
		PESO \ WEIGHT:	Scale \ SCALE: <b>Mod.P023_07</b>
			METODO 1 (ISO 128) METHOD 1 (ISO 128)
			REVISIONE: REVISION:
			
			 <b>FASTENERS &amp; TOOLS</b> RIVIT.IT