


ITEM TECHNICAL CARD

A (mm)	23,5
C (mm)	15,8
Schraubendurchmesser	4,2
E (mm)	0,6
Modell	U42-400
B (mm)	11,0
Modell	PAU42-400
s - Blechdicke (mm)	3,5 - 4,0
bilden	B

DESCRIZIONE \ DESCRIPTION: U42-400-Self threading plate gr 3,5-4,0 Unrefined d.4,2				CATEGORIA \ CATEGORY: 22459GR	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:		
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW		
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4	METODO 1 (ISO 128) METHOD 1 (ISO 128)
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07	REVISIONE: REVISION: 



**FASTENERS
& TOOLS**
RIVIT.IT