


ITEM TECHNICAL CARD



Anfangslochdurchmesser (mm)	28
Modell	S250
Gewicht (kg)	2,2 (senza cavo)
Motornennleistung (W)	550
minimaler Radius (mm)	20
Stahldicke 400N/mm ² (mm)	2,5
Aluminium Dicke 250N/mm ² (mm)	3,0
Stahldicke 600N/mm ² (mm)	2,0
Stahldicke 800N/mm ² (mm)	1,5
Trumpf code	A1942384

DESCRIZIONE \ DESCRIPTION: TRUMPF-Cesoia elettrica S 250 A1942384			CATEGORIA \ CATEGORY: 2288600	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:	
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW	
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07
			FASTENERS & TOOLS RIVIT.IT	