


ITEM TECHNICAL CARD



Lochdurchmesser (mm)	5,0
T - Kopfbreite	15,0
k - Kopf Dicke (mm)	2,2
Schiere Stärke (N)	3500
Zugbruchlast (N)	2000
Klemmbereich (mm)	20,0 ÷ 22,0
L (mm)	25,0
d - Durchmesser (mm)	4,8

DESCRIZIONE \ DESCRIPTION: RCAI-Aluminium/stainless steel hammer-drive rivet 4,8x25 T15			CATEGORIA \ CATEGORY: 2705600.02500	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:	
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW	
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07
			FASTENERS & TOOLS RIVIT.IT	