


ITEM TECHNICAL CARD



Lochdurchmesser (mm)	9,3 - 9,6
Durchmesser (mm)	M6
Modell	RSCFFL060
L - länge (mm)	12
minimale Lochtiefe (mm)	15,0
A x h (mm)	10,0 x 1,25
a x h (mm)	6,0 x 1,0

DESCRIZIONE \ DESCRIPTION: <b>RSCF-F-Self tapping socketGalv. Steel w/hole f.10 M6x1x12 - 0318L</b>		CATEGORIA \ CATEGORY: <b>2791200</b>	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:	NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	METODO 1 (ISO 128) METHOD 1 (ISO 128)
		PESO \ WEIGHT:	REVISIONE: REVISION:
		FOGLIO \ SHEET: <b>1 OF 1</b>	CARTIGLIO \ FORMAT <b>Mod.P023_07</b>
		FORMATO FOGLIO: SHEET FORMAT: <b>A4</b>	



**FASTENERS  
& TOOLS**  
RIVIT.IT