




ITEM TECHNICAL CARD

Lochdurchmesser (mm)	8,2 - 8,4
durchmesser der bolzen (mm)	8,0
T - Kopfbreite (mm)	16,7
L1 - Bolzenlänge (mm)	77,0
L2 (mm)	43,6 - 45,2
K - épaisseur de la tête (mm)	5,2
Schiere Stärke (N)	13000
Modell	RLAT10-20
Zugbruchlast (N)	12500
Klemmbereich (mm)	28,6 ÷ 34,9

DESCRIZIONE \ DESCRIPTION: <b>RIVLOCK-Lockbolt Aluminium DH d.10 gr 28,6-34,9 RLAT 10-20 d8</b>			CATEGORIA \ CATEGORY: <b>2842000</b>	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:	
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>	
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: <b>1 OF 1</b>	FORMATO FOGLIO: SHEET FORMAT: <b>A4</b>
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT <b>Mod.P023_07</b>
				
				  <b>FASTENERS &amp; TOOLS</b>  <b>RIVIT.IT</b>