


ITEM TECHNICAL CARD

| | |
|-------------|------------------------------|
| TX | 25 |
| Länge (mm) | 80/50,0 |
| Material | gelb verzinkter Stahl C10B21 |
| Durchmesser | 5,0 |
| pitch | 3,2 |
| D max (mm) | 10,0 |
| d1 (mm) | 3,7 |

| | | | | | |
|---|-------|--|---|---|---|
| DESCRIZIONE \ DESCRIPTION: Truciolare perforante rapid svasante TSP TX T25 ZG 5x80/50 | | | | CATEGORIA \ CATEGORY: 29959ZG.00200 | |
| MATERIAL \ MATERIAL: | | TRATTAMENTO TERMICO \ HEAT TREATMENT: | | NOTE \ NOTES: | |
| ESEGUITO DA \ DRAWN BY: RIVIT | DATA: | TRATT. SUPERFICIALE \ SURF. TREATMENT: | Rugosità superficiale generale: General surface roughness: | | |
| CONTROLLATO DA \ CHECKED BY: RIVIT | DATA: | PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]: | NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW | | |
| APPROVATO DA \ APPROVED BY: RIVIT | DATA: | DUREZZA \ HARDNESS: | FOGLIO \ SHEET: 1 OF 1 | FORMATO FOGLIO: SHEET FORMAT: A4 | METODO 1 (ISO 128) METHOD 1 (ISO 128) REVISIONE: REVISION: |
| | | PESO \ WEIGHT: | Scale \ SCALE: | CARTIGLIO \ FORMAT Mod.P023_07 |  |



**FASTENERS
& TOOLS**
RIVIT.IT