


ITEM TECHNICAL CARD



Lochdurchmesser (mm)	6,6 - 6,8
durchmesser der bolzen (mm)	6,4
T - Kopfbreite (mm)	13,4
L1 - Bolzenlänge (mm)	78,6
L2 (mm)	47,2 - 48,9
K - épaisseur de la tête (mm)	3,9
Schiere Stärke (N)	13500
Modell	RLFT08-25
Zugbruchlast (N)	13300
Klemmbereich (mm)	38,1 ÷ 41,3

DESCRIZIONE \ DESCRIPTION: <b>RIVLOCK-Lockbolt Steel DH d.6,4 gr 38,1-41,3 RLFT 8-25 d6,4</b>		CATEGORIA \ CATEGORY: <b>3007400</b>	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:	NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	METODO 1 (ISO 128) REVISIONE: METHOD 1 (ISO 128) REVISION:
		PESO \ WEIGHT:	Scale \ SCALE: <b>Mod.P023_07</b>



**FASTENERS  
& TOOLS**  
RIVIT.IT