

ITEM TECHNICAL CARD



Lochdurchmesser (mm)	9,8 - 10,0
durchmesser der bolzen (mm)	9,6
T - Kopfbreite (mm)	20,0
L1 - Bolzenlänge (mm)	65,0
L2 (mm)	27,1 - 28,8
K - épaisseur de la tête (mm)	6,4
Schiere Stärke (N)	30500
Modell	RLFT12-09
Zugbruchlast (N)	28000
Klemmbereich (mm)	11,1 ÷ 17,5

DESCRIZIONE \ DESCRIPTION: RIVLOCK-Lockbolt Steel DH d.10,0 gr 11,1-17,5 RLFT 12-9 d10		CATEGORIA \ CATEGORY: 3025700	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:	NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	METODO 1 (ISO 128) REVISIONE: METHOD 1 (ISO 128) REVISION:
		PESO \ WEIGHT:	Scale \ SCALE: Mod.P023_07



**FASTENERS
& TOOLS**
RIVIT.IT