

ITEM TECHNICAL CARD



Lochdurchmesser (mm)	5,0 - 5,2
durchmesser der bolzen (mm)	4,8
T - Kopfbreite (mm)	10,0
L1 - Bolzenlänge (mm)	60,5
L2 (mm)	31,4 - 33,1
K - épaisseur de la tête (mm)	3,2
Schiere Stärke (N)	10800
Modell	RLFT06-16
Zugbruchlast (N)	9700
Klemmbereich (mm)	23,8 ÷ 27,0

DESCRIZIONE \ DESCRIPTION: RIVLOCK-Lockbolt Steel d.4,8 gr 23,8-27,0 DH RLFT 6-16 d4,8		CATEGORIA \ CATEGORY: 3333300	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:	NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	METODO 1 (ISO 128) REVISIONE: METHOD 1 (ISO 128) REVISION:
		PESO \ WEIGHT:	Scale \ SCALE: Mod.P023_07



**FASTENERS
& TOOLS**
RIVIT.IT