



ITEM TECHNICAL CARD



Lochdurchmesser (mm)	5,0 - 5,2
durchmesser der bolzen (mm)	4,8
T - Kopfbreite (mm)	10,0
L1 - Bolzenlänge (mm)	64,0
L2 (mm)	34,6 - 36,3
K - épaisseur de la tête (mm)	3,2
Schiere Stärke (N)	10800
Modell	RLFT06-18
Zugbruchlast (N)	9700
Klemmbereich (mm)	27,0 ÷ 30,2

DESCRIZIONE \ DESCRIPTION: <b>RIVLOCK-Lockbolt Steel d.4,8 gr 27,0-30,2 DH RLFT 6-18 d4,8</b>			CATEGORIA \ CATEGORY: <b>3333400</b>	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:	
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>	
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: <b>1 OF 1</b>	FORMATO FOGLIO: SHEET FORMAT: <b>A4</b>
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT <b>Mod.P023_07</b>
			 	



**FASTENERS  
& TOOLS**  
RIVIT.IT