

ITEM TECHNICAL CARD



Lochdurchmesser (mm)	6,6 - 6,8
durchmesser der bolzen (mm)	6,4
T - Kopfbreite (mm)	13,4
L1 - Bolzenlänge (mm)	67,5
L2 (mm)	36,9 - 38,6
K - épaisseur de la tête (mm)	3,9
Schiere Stärke (N)	13500
Modell	RLFT08-18
Zugbruchlast (N)	13300
Klemmbereich (mm)	27,0 ÷ 30,2

DESCRIZIONE \ DESCRIPTION: RIVLOCK-Lockbolt Steel d.6,4 gr 27,0-30,2 DH RLFT 8-18 d6,4		CATEGORIA \ CATEGORY: 3334200	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:	NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	METODO 1 (ISO 128) REVISIONE: METHOD 1 (ISO 128) REVISION:
		PESO \ WEIGHT:	Scale \ SCALE: Mod.P023_07



**FASTENERS
& TOOLS**
RIVIT.IT