


ITEM TECHNICAL CARD

Öffnung (mm)	38 - 64
Modell	PG635V
Gewicht (kg)	0,5
Gewinde	M8
Rillentiefe (mm)	76
OAL (mm)	216
oberes V-Lager	einstellbar
unteres V-Lager	magnetico - 0°/45° ruotabile

DESCRIZIONE \ DESCRIPTION: STRONGHAND Pipe Plier Adjustable Top Pad, Magnetic Bottom Pad				CATEGORIA \ CATEGORY:		5170900	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:			
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:				
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW				
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4	METODO 1 (ISO 128) METHOD 1 (ISO 128)	REVISIONE: REVISION:	FASTENERS & TOOLS RIVIT.IT
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07	