



ITEM TECHNICAL CARD



Modell	UG125M-C3
Gewicht (kg)	2,1
Kapazität (mm)	320
Rillentiefe (mm)	120
Arbeitsdruck (kg)	550
Lager	standard
führen Dimension (mm)	25 x 12
Gewindebohrung	M10

DESCRIZIONE \ DESCRIPTION: STRONGHAND 4-IN-1 Clamp Cap.320mm Throat 120mm UG125M-		CATEGORIA \ CATEGORY: 5175400	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:	NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FUOGGIO \ SHEET: 1 OF 1
		PESO \ WEIGHT:	FORMATO FOGGIO: A4
		Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07
			METODO 1 (ISO 128) METHOD 1 (ISO 128)
			REVISIONE: REVISION:
			 FASTENERS & TOOLS  RIVIT.IT