

ITEM TECHNICAL CARD



Modell	UG125M-C3
Gewicht (kg)	2,1
Kapazität (mm)	320
Rillentiefe (mm)	120
Arbeitsdruck (kg)	550
Lager	standard
führen Dimension (mm)	25 x 12
Gewindebohrung	M10

DESCRIZIONE \ DESCRIPTION: <b>STRONGHAND 4-IN-1 Clamp Cap.320mm Throat 120mm UG125M-</b>		CATEGORIA \ CATEGORY: <b>5175400</b>	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:	NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	METODO 1 (ISO 128) REVISIONE: METHOD 1 (ISO 128) REVISION:
		PESO \ WEIGHT:	Foglio \ SHEET: <b>1 OF 1</b> Scale \ SCALE: FORMATO FOGLIO: <b>A4</b> SHEET FORMAT: CARTIGLIO \ FORMAT <b>Mod.P023_07</b>



**FASTENERS  
& TOOLS**  
RIVIT.IT