



ITEM TECHNICAL CARD

Dimension (mm)	1909x740x1068
Modell	LBT125
Faltenbreite max (mm)	1290
Gewicht (kg)	85
Dicke max Aluminiumblechs (mm)	15/10
Dicke max Kupferblechs (mm)	12,5/10
Dicke max Stahlblech (mm)	10/10

DESCRIZIONE \ DESCRIPTION: <b>SCHECHTL-Bending machine 1,25mt LBT125</b>				CATEGORIA \ CATEGORY:		<b>5321400</b>		
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:		  <b>FASTENERS &amp; TOOLS</b>  <b>RIVIT.IT</b>		
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:					
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	<b>NON SCALARE IL DISEGNO</b> <b>DO NOT RESIZE THE DRAW</b>					
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: <b>1 OF 1</b>	FORMATO FOGLIO: SHEET FORMAT: <b>A4</b>	METODO 1 (ISO 128) METHOD 1 (ISO 128)			REVISIONE: REVISION:
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT <b>Mod.P023_07</b>	