




ITEM TECHNICAL CARD



Länge (mm)	60,0
Durchmesser	6,3
pitch	1,8
UNI	6950
DIN	3928
k (mm)	5,15
S (mm)	10,0
b (mm)	1,0
Normative Beschreibung	Sechskantkopf Blechschraube mit Paspel
e min (mm)	10,95
d1 min (mm)	12,2
d1 max (mm)	13,2

DESCRIZIONE \ DESCRIPTION: Hexagon flange head self-tapping screw U6950/D6928 A2 - Stainless			CATEGORIA \ CATEGORY: 5611100.01000	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:	
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW	
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07
			 FASTENERS & TOOLS  RIVIT.IT	