



ITEM TECHNICAL CARD

Länge (mm)	50,0
Material	Rohstahl 8.8
Durchmesser	M14
UNI	5739
DIN	933
ISO	4017
k (mm)	8,8
Normative Beschreibung	Vollfilet Sechskantkopfschraube
s (mm)	22,0
e min (mm)	24,49
faden	2

DESCRIZIONE \ DESCRIPTION: <b>Hex head bolt ISO 4017/DIN 933 8.8 plain steel M14x50</b>				CATEGORIA \ CATEGORY:		<b>57752GR.00050</b>	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:			
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:				
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:		<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>			
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: <b>1 OF 1</b>	FORMATO FOGLIO: SHEET FORMAT: <b>A4</b>	METODO 1 (ISO 128) METHOD 1 (ISO 128)	REVISIONE: REVISION:	
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT <b>Mod.P023_07</b>	