

ITEM TECHNICAL CARD

TX	20
Länge (mm)	8,0
C max (mm)	4,06
Material	weiß verzinkter Stahl C15
Durchmesser	M4
pitch	0,7
UNI	8112
DIN	7500C
ISO	15480
k (mm)	3,2
d1 (mm)	8,0

DESCRIZIONE \ DESCRIPTION: Thread Rolling Screw T-Drive Pan Head U8112/D7500C white zinc		CATEGORIA \ CATEGORY: 59888ZB.01000	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:	NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FUOGIO \ SHEET: 1 OF 1
		PESO \ WEIGHT:	FORMATO FOGGIO: A4
		Scale \ SCALE:	METODO 1 (ISO 128) METHOD 1 (ISO 128)
		CARTIGLIO \ FORMAT Mod.P023_07	REVISIONE: REVISION:



**FASTENERS
& TOOLS**
RIVIT.IT