


ITEM TECHNICAL CARD

TX	25
Länge (mm)	8,0
C max (mm)	5,09
Material	weiß verzinkter Stahl C15
Durchmesser	M5
pitch	0,8
UNI	8112
DIN	7500C
ISO	15480
k (mm)	3,9
d1 (mm)	10,0

DESCRIZIONE \ DESCRIPTION: Trilobata TC TX25 UNI 8112/DIN 7500C ZB M5x8				CATEGORIA \ CATEGORY: 59940ZB.01000	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:	
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:		
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW		
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4	METODO 1 (ISO 128) METHOD 1 (ISO 128)
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07	REVISIONE: REVISION: 



**FASTENERS
& TOOLS**
RIVIT.IT