




ITEM TECHNICAL CARD

Dimension (mm)	25x25
Modell	RGT2525/60
Getreide	60
Material	Aluminiumoxid-Leinwand
rpm max	25000
verwenden	Stahl, Aluminium, Holz, Gusseisen

DESCRIZIONE \ DESCRIPTION: FERVI-Aluminium oxide shaft-mounted cloth wheels Alox 25x25/60			CATEGORIA \ CATEGORY:		6278600	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:		
ESEGUITO DA \ DRAWN BY: RIVIT	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:			
CONTROLLATO DA \ CHECKED BY: RIVIT	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW			
APPROVATO DA \ APPROVED BY: RIVIT	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: 1 OF 1	FORMATO FOGLIO: SHEET FORMAT: A4	METODO 1 (ISO 128) METHOD 1 (ISO 128)	REVISIONE: REVISION:
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT Mod.P023_07		FASTENERS & TOOLS  RIVIT.IT