

ITEM TECHNICAL CARD



hole diameter (mm)	2,5
d - rivet diameter	2,4
T - head width (mm)	4,8
L - rivet length (mm)	9,0
shear strength (N)	400
tensile strength (N)	500
grip range (mm)	4,5 ÷ 6,5
body material	aluminium
mandrel material	steel
head type	countersunk

DESCRIZIONE \ DESCRIPTION: <b>AFS-Blind rivet Alu/Steel CSKH4,8 2,4x9,0</b>			CATEGORIA \ CATEGORY: <b>0015200.15000</b>	
MATERIAL \ MATERIAL:		TRATTAMENTO TERMICO \ HEAT TREATMENT:		NOTE \ NOTES:
ESEGUITO DA \ DRAWN BY: <b>RIVIT</b>	DATA:	TRATT. SUPERFICIALE \ SURF. TREATMENT:	Rugosità superficiale generale: General surface roughness:	
CONTROLLATO DA \ CHECKED BY: <b>RIVIT</b>	DATA:	PROFONDITÀ TRATTAMENTO TERMICO (SURF) [mm]: HEAT TREATMENT (SURF) DEPTH [mm]:	<b>NON SCALARE IL DISEGNO DO NOT RESIZE THE DRAW</b>	
APPROVATO DA \ APPROVED BY: <b>RIVIT</b>	DATA:	DUREZZA \ HARDNESS:	FOGLIO \ SHEET: <b>1 OF 1</b>	FORMATO FOGLIO: SHEET FORMAT: <b>A4</b>
		PESO \ WEIGHT:	Scale \ SCALE:	CARTIGLIO \ FORMAT <b>Mod.P023_07</b>
			<b>FASTENERS &amp; TOOLS</b>  <b>RIVIT.IT</b>	